

## Alu-Ramp HD Range

With edge version

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Height of raised side mm	Weight of ramp pair kg
		1500	1750	2000						
900	H 135/30B	6885	7200	7200	3285	3000	320	375	30	71
1000	H 135/32B	6045	7090	7200	3075	3200	320	375	30	76
1100	H 135/35B	5120	5850	6825	2810	3500	320	375	30	81
1200	H 135/40B	4065	4520	5085	2805	4000	320	375	30	94
1400	H 135/45B	3365	3670	4035	2490	4500	320	375	30	105

900	H 135/30BL	6885	7200	7200	3285	3000	350	405	30	74
1000	H 135/32BL	6045	7090	7200	3075	3200	350	405	30	78
1100	H 135/35BL	5120	5850	6825	2810	3500	350	405	30	83
1200	H 135/40BL	4065	4520	5085	2805	4000	350	405	30	97
1400	H 135/45BL	3365	3670	4035	2490	4500	350	405	30	108

900	H 135/30BL1	6885	7200	7200	3285	3000	400	455	30	78
1000	H 135/32BL1	6045	7090	7200	3075	3200	400	455	30	83
1100	H 135/35BL1	5120	5850	6825	2810	3500	400	455	30	89
1200	H 135/40BL1	4065	4520	5085	2805	4000	400	455	30	103
1400	H 135/45BL1	3365	3670	4035	2490	4500	400	455	30	115

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Height of raised side mm	Weight of ramp pair kg
		1500	1750	2000						
1100	H 175/35B	6960	7955	8719	4240	3500	400	480	37	99
1200	H 175/40B	5520	6135	6900	4230	4000	400	480	37	112
1400	H 175/45B	4555	4970	5465	3755	4500	400	480	37	123
1500	H 175/50B	3860	4155	4505	3370	5000	400	480	37	135

1100	H 175/35BL	6960	7955	8719	4240	3500	500	580	37	108
1200	H 175/40BL	5520	6135	6900	4230	4000	500	580	37	123
1400	H 175/45BL	4555	4970	5465	3755	4500	500	580	37	135
1500	H 175/50BL	3860	4155	4505	3370	5000	500	580	37	148

## Alu-Ramp HD Range

With edge version

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Height of raised side mm	Weight of ramp pair kg
		1500	1750	2000						
1100	H 190/35B	9700	10450	10450	5865	3500	500	595	43	131
1200	H 190/40B	7700	8580	9650	5855	4000	500	595	43	152
1400	H 190/45B	6400	6980	7680	5200	4500	500	595	43	167
1500	H 190/50B	5450	5870	6360	4675	5000	500	595	43	183

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Height of raised side mm	Weight of ramp pair kg
		1500	1750	2000						
1200	H 220/40B	12000	12000	12000	8350	4000	500	580	50	163
1400	H 220/45B	9600	12000	12000	7415	4500	500	580	50	180
1500	H 220/50B	8175	8800	9535	6670	5000	500	580	50	200

1200	H 220/40BL	12000	12000	12000	8350	4000	550	625	50	168
1400	H 220/45BL	9600	12000	12000	7415	4500	550	625	50	186
1500	H 220/50BL	8175	8800	9535	6670	5000	550	625	50	206

## Without edge version

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Weight of ramp pair kg
		1500	1750	2000					
900	H 135/30S	6855	7200	7200	3285	3000	310	390	71
1000	H 135/32S	6045	7090	7200	3075	3200	310	390	76
1100	H 135/35S	5120	5850	6825	2810	3500	310	390	81
1200	H 135/40S	4065	4520	5085	2805	4000	310	390	94
1400	H 135/45S	3365	3670	4035	2490	4500	310	390	105

900	H 135/30SL	6855	7200	7200	3285	3000	340	420	74
1000	H 135/32SL	6045	7090	7200	3075	3200	340	420	78
1100	H 135/35SL	5120	5850	6825	2810	3500	340	420	84
1200	H 135/40SL	4065	4520	5085	2805	4000	340	420	98
1400	H 135/45SL	3365	3670	4035	2490	4500	340	420	108

## Alu-Ramp HD Range

With edge version

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Weight of ramp pair kg
		1500	1750	2000					
900	H 135/30SL1	6855	7200	7200	3285	3000	390	470	77
1000	H 135/32SL1	6045	7090	7200	3075	3200	390	470	81
1100	H 135/35SL1	5120	5850	6825	2810	3500	390	470	87
1200	H 135/40SL1	4065	4520	5085	2805	4000	390	470	101
1400	H 135/45SL1	3365	3670	4035	2490	4500	390	470	112

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Weight of ramp pair kg
		1500	1750	2000					
1100	H 175/35S	6960	7955	8719	4240	3500	400	480	99
1200	H 175/40S	5520	6135	6900	4230	4000	400	480	112
1400	H 175/45S	4555	4970	5465	3755	4500	400	480	123
1500	H 175/50S	3860	4155	4505	3370	5000	400	480	135

1100	H 175/35SL	6960	7955	8719	4240	3500	500	580	108
1200	H 175/40SL	5520	6135	6900	4230	4000	500	580	123
1400	H 175/45SL	4555	4970	5465	3755	4500	500	580	135
1500	H 175/50SL	3860	4155	4505	3370	5000	500	580	148

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Weight of ramp pair kg
		1500	1750	2000					
1100	H 190/35S	9700	10450	10450	5865	3500	500	610	132
1200	H 190/40S	7700	8580	9650	5855	4000	500	610	152
1400	H 190/45S	6400	6980	7680	5200	4500	500	610	167
1500	H 190/50S	5450	5870	6360	4675	5000	500	610	184

1200	H 220/40S	12000	12000	12000	8350	4000	500	620	169
1400	H 220/45S	9600	12000	12000	7415	4500	500	620	186
1500	H 220/50S	8175	8800	9535	6670	5000	500	620	206