

## Alu-Ramp Midi Range

Without edge version

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Weight of ramp pair kg
		750	1000	1250					
500	H 72/15S	1685	1685	1685	1685	1500	250	310	18
600	H 72/20S	1600	1600	1600	1265	2000	250	310	23
800	H 72/25S	1360	1590	1600	1010	2500	250	310	28
900	H 72/30S	1050	1180	1350	840	3000	250	310	33
1100	H 72/35S	849	936	1036	715	3500	250	310	39

500	H 72/15SL	1685	1685	1685	1685	1500	450	510	24
600	H 72/20SL	1600	1600	1600	1265	2000	450	510	30
800	H 72/25SL	1360	1590	1600	1010	2500	450	510	36
900	H 72/30SL	1050	1180	1350	840	3000	450	510	43
1100	H 72/35SL	849	936	1036	715	3500	450	510	50

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Weight of ramp pair kg
		1000	1250	1500					
800	H 100/25S	3600	3600	3600	2250	2500	300	370	38
900	H 100/30S	2800	3150	3350	1850	3000	300	370	45
1000	H 100/32S	2550	2850	3300	1750	3200	300	370	47
1100	H 100/35S	2200	2450	2750	1590	3500	300	370	51
1200	H 100/40S	1850	2000	2200	1590	4000	300	370	57

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Weight of ramp pair kg
		1000	1250	1500					
800	H 110/25S	3810	3810	3810	2250	2500	305	385	42
900	H 110/30S	3310	3700	3950	2050	3000	305	385	50
1000	H 110/32S	3050	3400	3780	2050	3200	305	385	52
1100	H 110/35S	2700	3000	3280	1950	3500	305	385	56
1200	H 110/40S	2330	2500	2700	1950	4000	305	385	63

## Alu-Ramp Midi Range

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Weight of ramp pair kg
		1000	1250	1500					
800	H 125/25S	4110	4110	4110	2055	2500	320	400	50
900	H 125/30S	3900	3900	3900	2055	3000	320	400	61
1000	H 125/32S	3600	3900	3900	2055	3200	320	400	65
1100	H 125/35S	3200	3500	3900	2055	3500	320	400	69
1200	H 125/40S	2600	2800	3100	2050	4000	320	400	80

800	H 125/25SL	4110	4110	4110	2055	2500	320	400	51
900	H 125/30SL	3900	3900	3900	2055	3000	320	400	62
1000	H 125/32SL	3600	3900	3900	2055	3200	320	400	66
1100	H 125/35SL	3200	3500	3900	2055	3500	320	400	71
1200	H 125/40SL	2600	2800	3100	2050	4000	320	400	81

### With edge version

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Height of raised side mm	Weight of ramp pair kg
		750	1000	1250						
500	H 72/15B	1685	1685	1685	1685	1500	250	310	24	18
600	H 72/20B	1600	1600	1600	1265	2000	250	310	24	23
800	H 72/25B	1360	1590	1600	1010	2500	250	310	24	28
900	H 72/30B	1050	1180	1350	840	3000	250	310	24	33
1100	H 72/35B	849	936	1036	715	3500	250	310	24	39

500	H 72/15BL	1685	1685	1685	1685	1500	450	510	24	24
600	H 72/20BL	1600	1600	1600	1265	2000	450	510	24	30
800	H 72/25BL	1360	1590	1600	1010	2500	450	510	24	36
900	H 72/30BL	1050	1180	1350	840	3000	450	510	24	43
1100	H 72/35BL	849	936	1036	715	3500	450	510	24	50

## Alu-Ramp Midi Range

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Height of raised side mm	Weight of ramp pair kg
		1000	1250	1500						
800	H 110/25B	3810	3810	3810	2250	2500	300	370	25	40
900	H 110/30B	3310	3700	3950	2050	3000	300	370	25	48
1000	H 110/32B	3050	3400	3780	2050	3200	300	370	25	50
1100	H 110/35B	2700	3000	3280	1950	3500	300	370	25	54
1200	H 110/40B	2330	2500	2700	1950	4000	300	370	25	61

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Height of raised side mm	Weight of ramp pair kg
		1000	1250	1500						
800	H 125/25B	4110	4110	4110	2055	2500	320	385	35	50
900	H 125/30B	3900	3900	3900	2055	3000	320	385	35	60
1000	H 125/32B	3600	3900	3900	2055	3200	320	385	35	64
1100	H 125/35B	3200	3500	3900	2055	3500	320	385	35	69
1200	H 125/40B	2600	2800	3100	2050	4000	320	385	35	79

800	H 125/25BL	4110	4110	4110	2055	2500	320	385	35	51
900	H 125/30BL	3900	3900	3900	2055	3000	320	385	35	61
1000	H 125/32BL	3600	3900	3900	2055	3200	320	385	35	65
1100	H 125/35BL	3200	3500	3900	2055	3500	320	385	35	70
1200	H 125/40BL	2600	2800	3100	2050	4000	320	385	35	80